


Datasheet for: 102753


Pressure transducer, - 250 bar, G 1/4, CrNi steel 1.4404

Pressure transducer for general industrial applications, Non-linearity 0.5%, Measurement range 0-250 bar, G 1/4, CrNi steel 1.4404 . Standard type for universal applications. Suitable for electronic pressure measurements in the low and high-pressure ranges.

Type number	895.27
Article number	102753
EAN/barcode	 4047322277266
Your price	192,31 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Electrical connection	With right-angle connector acc. to DIN EN 175301-803 A
Housing	CrNi steel 1.4404
Max. ambient temperature	80 °C
Max. medium temperature	80 °C
Measuring range max. bar	250.0
Measuring range min. bar	0.0
Nonlinearity	0.5% of span
Operating voltage	8 to 30 V
Output signal	4 - 20 mA, 2-wire
Page No.	HK235
Protection IP	IP 65 acc. to EN 60529
Thread	G 1/4
Type	A-10
Wetted parts	CrNi steel 1.4404

Variants

<i>Article number</i>	<i>Measuring range max. bar</i>	<i>Price</i>
102753	250.0	192,31 € / Stk
102745	6.0	192,31 € / Stk
102746	10.0	192,31 € / Stk
102747	16.0	192,31 € / Stk
102744	4.0	192,31 € / Stk
102750	60.0	192,31 € / Stk
102754	400.0	192,31 € / Stk
102752	160.0	192,31 € / Stk
102755	600.0	192,31 € / Stk
102743	2.5	192,31 € / Stk
102751	100.0	192,31 € / Stk
102748	25.0	192,31 € / Stk
102741	1.0	192,31 € / Stk
102749	40.0	192,31 € / Stk
102742	1.6	192,31 € / Stk