


Datasheet for: 101626


Condensate drain line »drukodrain plus« Level contr., 230 V/50 Hz

Condensate drain line »drukodrain plus«, Level controlled, Voltage 230 V / 50 Hz, Operating pressure 0.2 - 16 bar . Compact and exceptionally reliable, level-controlled drain for compressed air condensate. The condensate enters the integrated collecting tank, in which the level is continuously monitored. When the condensate reaches the maximum mark, the pilot valve opens and the condensate is forced into the discharge line by the system pressure. The valve closes again when the level reaches the minimum mark. Benefits of »drukodrain plus«: - No pressure loss - Diaphragm protected by integrated cup filter - Test button for manual outlet - Auto-reset function - Suitable for all condensate types

Type number	KA 20
Article number	101626
EAN/barcode	 4047322205177
Your price	196,81 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Compressor capacity	10 m ³ /min
Dryer capacity	20 m ³ /min
Filter capacity	100 m ³ /min
Max. operating pressure	16 bar
Min. operating pressure	0.2 bar
Page No.	HK182
Protection IP	IP 65
Voltage	230 V AC / 50 Hz