

Datasheet for: 159748



**Stainless steel ball valve, Pneumat. actuation drive, T-hole T2**

3-way stainless steel ball valve, Pneumat. actuation drive, T-hole T2, Operating temp. -20 °C to 70 °C, Rp 1/2, PN max. 63 bar . 3-way cock, reduced bore. Pneumatic actuators, double- or single acting version and integrated end-position feedback. Standardised interfaces: Actuator/valve interface: Four or eight female threads in the actuator housing acc. to EN ISO 5211. Actuator/control valve interface: Acc. to NAMUR or VDI/VDE 3845. Actuator/signalling device interface: Acc. to VDI/VDE 3845 (NAMUR).

Type number KHRP12ESANTDT2

Article number 159748

EAN/barcode



4047322643740

Your price 361,05 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	116.0 mm
Angle of rotation	90 °
B	130.0 mm
D	20.0 mm
DN	15.0
L	73.0 mm
Material actuator	Anodised aluminium
Material ball valve	Stainless steel 1.4401, with ISO flange plate
Max. operating pressure	63 bar
Max. operating temperature	70 °C
Max. pilot pressure	5.5 bar
Min. operating temperature	-20 °C
Page No.	HK303
Position	T 2
Sealant actuator	NBR
Sealant ball valve	PTFE / FKM
Thread	Rp 1/2

Valve adapter  
Version  
a/f

Acc. to NAMUR  
double-acting  
27 mm

## Variants

Article number	Thread	DN	a/f	Price
159748	Rp 1/2	15.0	27 mm	361,05 € / Stk
103633	Rp 3/4	20.0	32 mm	391,99 € / Stk
103634	Rp 1	25.0	41 mm	481,67 € / Stk
103635	Rp 1 1/4	32.0	50 mm	636,72 € / Stk
103636	Rp 1 1/2	40.0	55 mm	718,02 € / Stk
103637	Rp 2	50.0	71 mm	997,82 € / Stk

## More Pictures

