


Datasheet for: 102966


3/2-way solenoid valve brass, NC, directly operated 24 V DC

3/2-way solenoid valve brass, NC, directly operated 24 V DC, Sealing material NBR, Rp 1/4, PN - 4 bar, I.D. 3.2 . For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Type number	MV 3212 G
Article number	102966
EAN/barcode	 4047322160773
Your price	151,37 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	80.0 mm
B	43.0 mm
DN	3.2
Electrical connection	For Pg 11P connector socket acc. to ISO 4400
Function	normally closed (NC)
Housing	Brass
Internal parts	Stainless steel
Max. ambient temperature	75 °C
Max. medium temperature	90 °C
Max. operating pressure	4 bar
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK327
Protection IP	IP65 (with connector socket fitted)
Sealant	NBR
Standard thread	Rp thread acc. to ISO 7-1
Thread	Rp 1/4
Type	10
Valve seat	Brass

Variants

Article number	Thread	Max. operating pressure	DN	Type	Price
102966	Rp 1/4	4 bar	3.2	10	151,37 € / Stk
102965	Rp 1/8	7 bar	2.4	7	119,98 € / Stk

More Pictures

