

Datasheet for: 103669


Intermediate flange blocking flap, Pneum. actuation drive, DN 65

Intermediate flange blocking flap, Pneumat. actuation drive, double-acting, Operating temp. -15°C to 120°C, DN 65, PN max. 16 bar . Butterfly valves with pneumatic actuator. Pneumatic actuators, double- or single acting version. For water/steam, seawater, salt water, ester, ketones, alkalis, caustic soda, sodium hydroxide. Not recommended for hydrocarbons, oils or greases.

Type number	350.4065B
Article number	103669
EAN/barcode	 4047322339049
Your price	265,12 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Angle of rotation	90 °
B	49.0 mm
DN	65.0
Disc	Stainless steel CF8M/1.4404
H1	78.0 mm
H2	155.0 mm
H3	259.0 mm
Housing	Grey cast iron GG25 epoxy resin coated, RAL 5015 color
L	115.0 mm
Material actuator	Anodised aluminium
Max. operating pressure	16 bar
Max. operating temperature	120 °C
Max. pilot pressure	5.5 bar
Min. operating temperature	-15 °C
Min. pilot pressure	5.0 bar
Page No.	HK307
Sealant	EPDM
Sealant actuator	NBR

Selector shaft
 Selector shaft
 seal
 Valve adapter
 Version

SS416
 EPDM
 Supplied as standard, operated by a 3/2- or 5/2-way valve
 double-acting

Variants

Article number	DN	Price
103669	65.0	265,12 € / Stk
103673	150.0	620,17 € / Stk
103668	50.0	248,23 € / Stk
103667	40.0	246,37 € / Stk
103672	125.0	430,19 € / Stk
103671	100.0	374,04 € / Stk
103670	80.0	283,43 € / Stk

More Pictures

