

Datasheet for: 105508



Corner safety valve, G 1 1/2, Trigger pressure 0.2 bar

Corner safety valve, for saturated steam, Red brass, Operating temp. -10 to 135 °C, G 1 1/2, AF 58, Trigger pressure 0.2 bar . Type-tested, TÜV – SV. 749 D/G

Type number	222.07-0,2
-------------	------------

Article number	105508
----------------	--------

EAN/barcode	
-------------	--



4047322040273

Your price	267,92 € / Stk
------------	----------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Adjustment range max.	20.0 bar
Adjustment range min.	0.2 bar
Diaphragms	EPDM
H	175.0 mm
Housing	Bronze
Inlet and outlet	Open
Internal parts	Brass
L1	48.0 mm
L2	40.0 mm
Max. operating temperature	135 °C
Min. operating temperature	-10 °C
Min. set pressure	0.2 bar
Page No.	HK366
Page No. SF	SF059
Spring	C steel
Spring bonnet	Brass
Thread	G 1 1/2
a/f	58 mm

Variants

Article number	Min. set pressure	Max. operating temperature	Diaphragms	Price
105508	0.2 bar	135 °C	EPDM	267,92 € / Stk
105510	2.0 bar	135 °C	EPDM	267,92 € / Stk
105512	2.5 bar	135 °C	EPDM	267,92 € / Stk
105513	3.0 bar	185 °C	PTFE	267,92 € / Stk
105514	4.0 bar	185 °C	PTFE	267,92 € / Stk
105509	0.7 bar	135 °C	EPDM	267,92 € / Stk
105511	2.2 bar	135 °C	EPDM	267,92 € / Stk
105515	5.0 bar	185 °C	PTFE	267,92 € / Stk
105516	6.0 bar	185 °C	PTFE	267,92 € / Stk
117643	8.0 bar	185 °C	PTFE	267,92 € / Stk
125305	0.4 bar	135 °C	EPDM	267,92 € / Stk
169708	4.5 bar	185 °C	PTFE	267,92 € / Stk
179736	1.0 bar	135 °C	EPDM	267,92 € / Stk

More Pictures

