

Datasheet for: 133552



**Stainless steel filter, 1.4401, 25  $\mu\text{m}$ , Size 3, G 3/4**

Stainless steel filter, 1.4401, 25  $\mu\text{m}$ , Size 3, G 3/4, Input pressure max. 30 bar, Medium temperature max. 80 °C .  
 Stainless steel filters for use in the chemical industry, mining, plant construction and special machinery industries, pneumatics, etc.

Type number 580FM3-34

Article number 133552

EAN/barcode



4047322479356

Your price 368,80 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	82.0 mm
B	170.0 mm
C	155.0 mm
Condensate drain	Locking screw
Filter rating	25.0 $\mu\text{m}$
Flow rate	5440 l/min
Flow rate measurement	At $P_1 = 6$ bar and pressure drop $\Delta_p \leq 1$ bar
Housing	Stainless steel 1.4401 (AISI 316)
Max. ambient temperature	60 °C
Max. input pressure	30 bar
Max. medium temperature	80 °C
Page No.	HK153
Sealant	NBR
Size	3
Thread	G 3/4

## Variants

Article number	Thread	Flow rate	Size	Price
133552	G 3/4	5440 l/min	3	368,80 € / Stk
133549	G 1/4	2155 l/min	1	290,05 € / Stk
133551	G 1/2	3485 l/min	3	368,80 € / Stk
133553	G 1	9960 l/min	4	1.031,31 € / Stk
133550	G 3/8	2380 l/min	1	290,05 € / Stk

## More Pictures

