


Datasheet for: 105625



**Corner safety valve, liquids, G 1 1/2, Trigger pressure 2 bar**

Corner safety valve, for liquids, Red brass, Operating temp. -10 °C to 110 °C, G 1 1/2, AF 58, Trigger pressure 2 bar . For non-toxic, non-flammable liquids. No evaporation allowed when blowing off. With diaphragm to protect the spring and with lifting device. Type-tested, TÜV-SV. 749. F

Type number	221.07-2,0
Article number	105625
EAN/barcode	 4047322039659
Your price	267,92 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Adjustment range max.	16.0 bar
Adjustment range min.	1.0 bar
Diaphragms	NBR
H	175.0 mm
Housing	Bronze
Inlet and outlet	Each with female thread acc. to DIN EN ISO 228-1
Internal parts	Brass
L1	48.0 mm
L2	40.0 mm
Max. operating temperature	110 °C
Min. operating temperature	-10 °C
Min. set pressure	2.0 bar
Page No.	HK367
Page No. SF	SF060
Spring	C steel
Spring bonnet	Brass
Thread	G 1 1/2
a/f	58 mm

## Variants

Article number	Min. set pressure	Price
105625	2.0 bar	267,92 € / Stk
105626	3.0 bar	267,92 € / Stk
105627	4.0 bar	267,92 € / Stk
105628	5.0 bar	267,92 € / Stk
105630	6.0 bar	267,92 € / Stk
105631	7.0 bar	267,92 € / Stk
105636	31.0 bar	267,92 € / Stk
105632	8.0 bar	267,92 € / Stk
105633	10.0 bar	267,92 € / Stk
105634	11.5 bar	267,92 € / Stk
105629	5.5 bar	267,92 € / Stk
105635	15.0 bar	267,92 € / Stk
130814	3.5 bar	267,92 € / Stk

## More Pictures

