


Datasheet for: 124854


Service unit 3-part »variobloc«, Protective cage, Size 1, G 1/4

Service unit 3-part »variobloc«, PC container and protective cage, Size 1, G 1/4, Input pressure max. 16 bar, Temp. max. 50 °C . Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator. Approved series in modern industrial design, with the following key benefits: - Simple handling - Convenient modular assembly thanks to innovative fasteners - Excellent flow values

Type number	VW 12 S
Article number	124854
EAN/barcode	 4047322398312
Your price	151,99 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	144.0 mm
B	201.0 mm
Bowl	Polycarbonate container with protective cage
C	68.0 mm
Condensate drain	Manual
Diaphragms	NBR
Filter rating	40.0 µm
Flow rate	1500 l/min
Flow rate measurement	At P ₁ = 10 bar, P ₂ = 6 bar and pressure drop Δ _p = 1 bar
Housing	Die-cast zinc
Max. ambient temperature	50 °C
Max. control range	10.0 bar
Max. input pressure	16 bar
Max. medium temperature	50 °C
Min. control range	0.5 bar
Page No.	WEB

Pressure gauge display max.	10.0 bar
Pressure gauge display min.	0.0 bar
Sealant	NBR
Series	variobloc
Sight dome	PA
Size	1
Spring bonnet	POM
Thread	G 1/4

Variants

Article number	Thread	Flow rate	Size	Price
124854	G 1/4	1500 l/min	1	151,99 € / Stk
124860	G 3/4	5000 l/min	2	223,10 € / Stk
124862	G 1	5000 l/min	2	257,58 € / Stk
124858	G 1/2	3400 l/min	2	223,10 € / Stk
124856	G 3/8	1800 l/min	1	151,99 € / Stk

More Pictures

