

## Datasheet for: 103595


**Stainless steel ball valve, Pneumat. actuation drive, Rp 1/2**

2-way stainless steel ball valve, Pneumat. actuation drive, double-acting, Operating temp. -20°C to 70°C, Rp 1/2, PN max. 63 bar . 2-way cock, 3-piece, full bore. Pneumatic actuators, double- or single acting version and integrated end-position feedback. Standardised interfaces:  
 Actuator/valve interface: Four or eight female threads in the actuator housing acc. to EN ISO 5211. Actuator/control valve interface: Acc. to NAMUR or VDI/VDE 3845.  
 Actuator/signalling device interface: Acc. to VDI/VDE 3845 (NAMUR).

Type number	350.510
Article number	103595
EAN/barcode	 4047322076463
Your price	268,03 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	133.0 mm
Angle of rotation	90 °
B	144.0 mm
D	24.0 mm
DN	15.0
L	75.0 mm
Material actuator	Anodised aluminium
Material ball valve	Stainless steel 1.4401, with ISO flange plate
Max. operating pressure	63 bar
Max. operating temperature	70 °C
Max. pilot pressure	5.5 bar
Min. operating temperature	-20 °C
Page No.	HK302
Sealant actuator	NBR
Sealant ball valve	PTFE
Thread	Rp 1/2

Valve adapter  
 Version  
 a/f

 Acc. to NAMUR  
 double-acting  
 29 mm

## Variants

Article number	Thread	DN	a/f	Price
103595	Rp 1/2	15.0	29 mm	268,03 € / Stk
103596	Rp 1/2	15.0	29 mm	229,12 € / Stk
103597	Rp 3/4	20.0	35 mm	284,58 € / Stk
103598	Rp 3/4	20.0	35 mm	244,75 € / Stk
103599	Rp 1	25.0	41 mm	347,24 € / Stk
103600	Rp 1 1/4	32.0	50 mm	415,05 € / Stk
103601	Rp 1 1/2	40.0	58 mm	474,81 € / Stk
103602	Rp 2	50.0	74 mm	542,73 € / Stk
103603	Rp 2 1/2	65.0	89 mm	943,44 € / Stk
103604	Rp 3	80.0	104 mm	1.209,50 € / Stk

## More Pictures

