


## Datasheet for: 101182


**Microfilter for high pressures up to 60 bar, 0.01  $\mu\text{m}$ , G 3/4**

Microfilter for high pressures up to 60 bar, manual bleeder valve, 0.01  $\mu\text{m}$ , G 3/4, Brass container, Operating temp. °C to 90 °C . Fine filter for all applications with particularly strict compressed air purity requirements. Micro-filters should always be used in conjunction with a standard filter connected upstream to trap coarse impurities and protect the micro-filter inserts.

Type number	680.43
Article number	101182
EAN/barcode	 4047322270366
Your price	269,09 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	92.0 mm
B	196.0 mm
Bowl	Brass
C	29.0 mm
Efficiency	99.9999 %
Filter element	Borosilicate
Filter rating	0.01 $\mu\text{m}$
Flow rate	2300 l/min
Flow rate measurement	At $P_2 = 6$ bar and pressure drop $\Delta_p = 0.5$ bar
Housing	Aluminium
Max. input pressure	60 bar
Max. operating temperature	90 °C
Page No.	HK144
Sealant	NBR
Thread	G 3/4

## Variants

Article number	Thread	Flow rate	Price
101182	G 3/4	2300 l/min	269,09 € / Stk
101183	G 1	2300 l/min	263,94 € / Stk
101181	G 1/2	2000 l/min	210,75 € / Stk
101180	G 3/8	2000 l/min	213,87 € / Stk

## More Pictures

