

Datasheet for: 133392


Blocking valve pneumat. actuated, double-acting NC, FKM, Rp 1 1/2

Blocking valve pneumat. actuated, double-acting, NC, nickel-plated brass, Temp. -20°C to 150°C, Control pressure 3-8 bar, Rp 1 1/2 . 2/2-way check valves, specially designed for automated industrial plant engineering. A low-price, compact, space-saving and reliable alternative to ball valves with a pneumatic rotary actuator. These valves have a full bore and - owing to the optimised design - only minimal flow losses. They are controlled by means of filtered compressed air.

Type number	351.926
Article number	133392
EAN/barcode	 4047322477895
Your price	273,23 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	NAMUR interface, direct: 2 x G 1/8
DN	40.0
H	96.0 mm
Housing	Nickel-plated brass
Internal parts	Nickel-plated brass
L	180.0 mm
Max. operating pressure	10 bar
Max. operating temperature	150 °C
Max. pilot pressure	8.0 bar
Min. operating temperature	-20 °C
Min. pilot pressure	3.0 bar
Mounting position	Any
Page No.	HK345
Sealant	FKM
Spring	Stainless steel
Thread	Rp 1 1/2
Version	double-acting

Variants

Article number	Thread	DN	Price
133392	Rp 1 1/2	40.0	273,23 € / Stk
103727	Rp 3/8	10.0	106,12 € / Stk
103728	Rp 1/2	15.0	116,26 € / Stk
103729	Rp 3/4	20.0	132,10 € / Stk
103730	Rp 1	25.0	151,67 € / Stk
133393	Rp 2	50.0	376,43 € / Stk
133391	Rp 1 1/4	32.0	218,25 € / Stk

More Pictures

