

## Datasheet for: 158761



**Stainless steel ball valve, Pneumatic actuation drive, Rp 1/2**

Stainless steel ball valve, Pneumatic actuation drive, single-acting, Operating temp. -20 °C to 150 °C, Rp 1/2, PN max. 100 bar . Ball valves with pneumatic actuator. Pneumatic, double-piston, part-turn actuator, double-rocker principle.

Type number	351.520-2
-------------	-----------

Article number	158761
----------------	--------

EAN/barcode



4047322634137

Your price	276,75 € / Stk
------------	----------------

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	233.2 mm
Angle of rotation	90 °
B	154.0 mm
DN	15.0
L	65.0 mm
Material actuator	Anodised aluminium
Material ball valve	Stainless steel 1.4401/1.4301/1.4310/1.4408, with ISO flange
Max. Operating pressure ball valve	150 °C
Max. operating temperature actuator	80 °C
Max. pilot pressure actuator	8.4 bar
Min. Operating pressure ball valve	-20 °C
Min. operating temperature actuator	-20 °C
PN	100 bar
Page No.	HK304
Recommended pilot pressure	5.6 bar
Sealant actuator	NBR

Sealant ball valve  
 Thread  
 Valve adapter  
 Version

PTFE / FKM  
 Rp 1/2  
 Integrated to NAMUR  
 single-acting - spring to close

## Variants

Article number	Thread	DN	PN	Price
158761	Rp 1/2	15.0	100 bar	276,75 € / Stk
158760	Rp 3/8	10.0	100 bar	272,84 € / Stk
158766	Rp 2	50.0	40 bar	701,48 € / Stk
158763	Rp 1	25.0	100 bar	363,00 € / Stk
158762	Rp 3/4	20.0	100 bar	337,50 € / Stk
158764	Rp 1 1/4	32.0	64 bar	431,25 € / Stk
158765	Rp 1 1/2	40.0	64 bar	510,27 € / Stk

## More Pictures

