


Datasheet for: 158060


Ball valve 3/2-way »variobloc«, pneumatic drive, Size 2, G 1

Ball valve 3/2-way »variobloc«, with pneumatic drive, with ventilation and silencer, Size 2, G 1, Operating pressure max. 25 bar . Used as the main shut-off element, especially for flanging onto the start of a variobloc service unit. The variant with pneumatic drive (size 2) allows the use even in poorly accessible areas as a remote control. With pressure relief and silencer.

Type number	VK 26-P
Article number	158060
EAN/barcode	 4047322631761
Your price	381,16 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	125.0 mm
B	120.0 mm
Flow rate	11000 l/min
Flow rate measurement	At $P_1 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Max. ambient temperature	80 °C
Max. operating pressure	25 bar
Max. pilot pressure	7.4 bar
Min. pilot pressure	5.6 bar
Page No.	HK112
Series	variobloc
Size	2
Thread	G 1

Variants

Article number	Thread	Flow rate	Price
158060	G 1	11000 l/min	381,16 € / Stk
158058	G 1/2	9000 l/min	350,10 € / Stk
158059	G 3/4	11000 l/min	350,10 € / Stk

More Pictures

