

Datasheet for: 137349



Stainless steel casting filter, 1.4401, 25 µm, Size 3, G 1/2

Stainless steel casting filter, 1.4401, 25 µm, Size 3, G 1/2, Input pressure max. 30 bar, Medium temperature max. 80 °C . Stainless steel filters for use in the chemical industry, mining, plant construction and special machinery industries, pneumatics, etc.

Type number 580FC3-12

Article number 137349

EAN/barcode



4047322513326

Your price 281,74 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	82.0 mm
B	133.0 mm
C	113.0 mm
Condensate drain	Locking screw
Filter rating	25.0 µm
Flow rate	5355 l/min
Flow rate measurement	At P ₁ = 6 bar and pressure drop $\Delta_p \leq 1$ bar
Housing	Stainless steel casting 1.4401 (AISI 316)
Max. ambient temperature	60 °C
Max. input pressure	30 bar
Max. medium temperature	80 °C
Page No.	HK154
Sealant	NBR
Size	3
Thread	G 1/2

Variants

Article number	Thread	Flow rate	Size	Price
137349	G 1/2	5355 l/min	3	281,74 € / Stk
137347	G 1/4	2010 l/min	1	242,08 € / Stk
137350	G 3/4	6855 l/min	3	281,74 € / Stk
137348	G 3/8	2920 l/min	1	242,08 € / Stk
137351	G 1	9910 l/min	4	904,13 € / Stk
137352	G 1 1/2	9910 l/min	4	904,13 € / Stk

More Pictures

