


Datasheet for: 101084


Service unit 3-part »Standard«, Metal container, Size 3, G 3/4

Service unit 3-part »Standard«, Metal container, metal drip cap, Size 3, G 3/4, Input press. max. 25 bar, Control range 0.5-16 bar . Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Type number	850 D/M
Article number	101084
EAN/barcode	 4047322121491
Your price	388,71 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	302.0 mm
B	230.5 mm
Bowl	Metal container
C	58.0 mm
Condensate drain	Manuel
DN	20.0
Filter rating	5.0 μ m
Flow rate	3200 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc / aluminium, painted silver
Max. ambient temperature	60 °C
Max. control range	16.0 bar
Max. input pressure	25 bar
Max. medium temperature	60 °C
Min. control range	0.5 bar
Page No.	HK132
Pressure gauge display max.	25.0 bar
Pressure gauge display min.	0.0 bar

Pressure gauge	63 mm
Ø	
Sealant	NBR
Series	Standard
Sight dome	Zinc-glass-NBR
Size	3
Thread	G 3/4

Variants

Article number	Thread	Filter rating	Flow rate	Size	DN	Price
101084	G 3/4	5.0 µm	3200 l/min	3	20.0	388,71 € / Stk
101080	G 1/4	5.0 µm	600 l/min	1	6.0	141,88 € / Stk
101081	G 3/8	5.0 µm	600 l/min	1	6.0	141,88 € / Stk
101082	G 3/8	40.0 µm	1400 l/min	2	6.0	195,35 € / Stk
101083	G 1/2	5.0 µm	3200 l/min	3	15.0	211,92 € / Stk
101085	G 1	5.0 µm	3200 l/min	3	25.0	388,71 € / Stk
101086	G 1 1/4	40.0 µm	5000 l/min	4	25.0	782,55 € / Stk
101087	G 1 1/2	40.0 µm	5000 l/min	4	35.0	745,06 € / Stk

More Pictures

