

## Datasheet for: 103670


**Intermediate flange blocking flap, Pneum. actuation drive, DN 80**

Intermediate flange blocking flap, Pneumat. actuation drive, double-acting, Operating temp. -15°C to 120°C, DN 80, PN max. 16 bar . Butterfly valves with pneumatic actuator. Pneumatic actuators, double- or single acting version. For water/steam, seawater, salt water, ester, ketones, alkalis, caustic soda, sodium hydroxide. Not recommended for hydrocarbons, oils or greases.

Type number	350.4080B
-------------	-----------

Article number	103670
----------------	--------

EAN/barcode	
-------------	--



4047322339056

Your price	283,43 € / Stk
------------	----------------

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Angle of rotation	90 °
B	47.0 mm
DN	80.0
Disc	Stainless steel CF8M/1.4404
H1	89.0 mm
H2	162.0 mm
H3	280.0 mm
Housing	Grey cast iron GG25 epoxy resin coated, RAL 5015 color
L	127.0 mm
Material actuator	Anodised aluminium
Max. operating pressure	16 bar
Max. operating temperature	120 °C
Max. pilot pressure	5.5 bar
Min. operating temperature	-15 °C
Min. pilot pressure	5.0 bar
Page No.	HK307
Sealant	EPDM
Sealant actuator	NBR

Selector shaft  
Selector shaft  
seal  
Valve adapter  
Version

SS416  
EPDM  
Supplied as standard, operated by a 3/2- or 5/2-way valve  
double-acting

## Variants

Article number	DN	Price
103670	80.0	283,43 € / Stk
103673	150.0	620,17 € / Stk
103669	65.0	265,12 € / Stk
103668	50.0	248,23 € / Stk
103667	40.0	246,37 € / Stk
103672	125.0	430,19 € / Stk
103671	100.0	374,04 € / Stk

## More Pictures

