


Datasheet for: 101122


Service unit »ONE« without pressure switch, G 1/4

Service unit »ONE« without pressure switch, G 1/4, Input pressure max. 10 bar, Control range 0.5 - 8 bar, Temp. -10 °C to 50 °C . Multifunctional service unit with 6 or 7 functions in a single device: 3/2-way valve (manually operated), filter with automatic drain valve, air ports, pressure regulator, pressure gauge, soft start valve and optional pressure switch This combination of extremely good flow rates and a wide range of functions integrated in a single, compact unit saves valuable space and is unmatched by any similar product available in the market! Soft starting independently of the load and easy replacement of the filter cartridge under pressure are just two of the other outstanding features of this amazing device.

| | |
|----------------|--|
| Type number | 533.301 |
| Article number | 101122 |
| EAN/barcode |  4047322284769 |
| Your price | 283,82 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|------------------------|--|
| A | 165.5 mm |
| B | 144.0 mm |
| C | 35.0 mm |
| Filter rating | 20.0 µm |
| Flow rate | 2400 l/min |
| Flow rate measurement | At P ₂ = 6.3 bar and pressure drop Δ _p = 1 bar |
| Max. control range | 8.0 bar |
| Max. input pressure | 10 bar |
| Max. temperature range | 50 °C |
| Medium | Pneumatics |
| Min. control range | 0.5 bar |
| Min. temperature range | -10 °C |
| Operating voltage | 24 V DC (for valves and pressure switch) |
| Page No. | HK136 |
| Protection IP | IP 65 |

Series
 Thread

 ONE
 G 1/4

Variants

| <i>Article number</i> | <i>Thread</i> | <i>Flow rate</i> | <i>Price</i> |
|-----------------------|---------------|------------------|----------------|
| 101122 | G 1/4 | 2400 l/min | 283,82 € / Stk |
| 101123 | G 3/8 | 3300 l/min | 283,82 € / Stk |
| 101124 | G 1/2 | 4000 l/min | 289,35 € / Stk |

More Pictures

