


Datasheet for: 101123


Service unit »ONE« without pressure switch, G 3/8

Service unit »ONE« without pressure switch, G 3/8, Input pressure max. 10 bar, Control range 0.5 - 8 bar, Temp. -10 °C to 50 °C . Multifunctional service unit with 6 or 7 functions in a single device: 3/2-way valve (manually operated), filter with automatic drain valve, air ports, pressure regulator, pressure gauge, soft start valve and optional pressure switch This combination of extremely good flow rates and a wide range of functions integrated in a single, compact unit saves valuable space and is unmatched by any similar product available in the market! Soft starting independently of the load and easy replacement of the filter cartridge under pressure are just two of the other outstanding features of this amazing device.

Type number	533.302
Article number	101123
EAN/barcode	 4047322284790
Your price	283,82 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	165.5 mm
B	144.0 mm
C	35.0 mm
Filter rating	20.0 µm
Flow rate	3300 l/min
Flow rate measurement	At P ₂ = 6.3 bar and pressure drop Δ _p = 1 bar
Max. control range	8.0 bar
Max. input pressure	10 bar
Max. temperature range	50 °C
Medium	Pneumatics
Min. control range	0.5 bar
Min. temperature range	-10 °C
Operating voltage	24 V DC (for valves and pressure switch)
Page No.	HK136
Protection IP	IP 65

Series
Thread

ONE
G 3/8

Variants

<i>Article number</i>	<i>Thread</i>	<i>Flow rate</i>	<i>Price</i>
101123	G 3/8	3300 l/min	283,82 € / Stk
101122	G 1/4	2400 l/min	283,82 € / Stk
101124	G 1/2	4000 l/min	289,35 € / Stk

More Pictures

