


Datasheet for: 103570



Brass ball valve, Pneumat. actuation drive, double-acting, Rp 2

Brass ball valve, Pneumat. actuation drive, double-acting, Operating temperature -20 °C to 150 °C, Rp 2, DN 50, PN max. 16 bar . Ball valves with pneumatic actuator. Pneumatic, double-piston, part-turn actuator, double-rocker principle.

Type number	351.215
Article number	103570
EAN/barcode	 4047322078719
Your price	284,35 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	130.0 mm
Angle of rotation	90 °
B	145.0 mm
DN	50.0
L	134.0 mm
Material actuator	Anodised aluminium
Material ball valve	Nickel-plated brass, with ISO flange plate
Max. operating pressure	16 bar
Max. operating temperature	150 °C
Max. pilot pressure	5.6 bar
Max. temperature range	80 °C
Min. operating temperature	-20 °C
Min. temperature range	-20 °C
Page No.	WEB
Sealant actuator	NBR
Sealant ball valve	PTFE / FKM
Thread	Rp 2
Valve adapter	Supplied as standard

Version double-acting

Variants

Article number	Thread	DN	Price
103570	Rp 2	50.0	284,35 € / Stk
103564	Rp 3/8	10.0	130,81 € / Stk
103565	Rp 1/2	15.0	132,80 € / Stk
103566	Rp 3/4	20.0	137,58 € / Stk
103567	Rp 1	25.0	144,91 € / Stk
103568	Rp 1 1/4	32.0	195,93 € / Stk
103569	Rp 1 1/2	40.0	219,46 € / Stk

More Pictures

