


Datasheet for: 158802



Brass ball valve, Pneumat. actuation drive, double-acting, Rp 2

Brass ball valve, Pneumat. actuation drive, NAMUR, double-acting, Operating temp. -20 °C to 150 °C, Rp 2, DN 50, PN max. 16 bar . Ball valves with pneumatic actuator. Pneumatic, double-piston, part-turn actuator, double-rocker principle.

Type number	351.215-1
Article number	158802
EAN/barcode	 4047322635332
Your price	285,12 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	174.2 mm
Angle of rotation	90 °
B	143.8 mm
DN	50.0
L	134.0 mm
Material actuator	Anodised aluminium
Material ball valve	Nickel-plated brass, with flange plate ISO 5211
Max. Operating pressure ball valve	150 °C
Max. operating pressure ball valve	16 bar
Max. operating temperature actuator	80 °C
Max. pilot pressure actuator	8.4 bar
Min. Operating pressure ball valve	-20 °C
Min. operating temperature actuator	-20 °C
Page No.	HK301
Recommended pilot pressure	5.6 bar

Sealant actuator	NBR
Sealant ball valve	PTFE / FKM
Thread	Rp 2
Valve adapter	Integrated to NAMUR
Version	double-acting

Variants

Article number	Thread	DN	Price
158802	Rp 2	50.0	285,12 € / Stk
158800	Rp 1 1/4	32.0	193,68 € / Stk
158831	Rp 1	25.0	149,16 € / Stk
158801	Rp 1 1/2	40.0	214,56 € / Stk
158829	Rp 1/2	15.0	131,76 € / Stk
158828	Rp 3/8	10.0	131,04 € / Stk
158830	Rp 3/4	20.0	141,24 € / Stk

More Pictures

