


Datasheet for: 103534


Brass ball valve, Pneumat. actuation drive spring switching, Rp 1

2-way brass ball valve, Pneumat. actuation drive spring switching, Operating temp. max. 70 °C, Rp 1, DN 25, PN max. 40 bar . 2-way cock, full bore. Pneumatic actuators, double- or single acting version and integrated end-position feedback.

Type number	350.312
Article number	103534
EAN/barcode	 4047322076029
Your price	285,87 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	133.0 mm
Angle of rotation	90 °
B	148.0 mm
D	25.0 mm
DN	25.0
L	90.0 mm
Material actuator	Anodised aluminium
Material ball valve	Nickel-plated brass, with ISO flange plate
Max. operating temperature	70 °C
Max. pilot pressure	5.5 bar
Min. operating temperature	-20 °C
PN	40 bar
Page No.	HK299
Sealant actuator	NBR
Sealant ball valve	PTFE / FKM
Thread	Rp 1
Valve adapter	Supplied as standard
Version	single-acting - spring to close
a/f	41 mm

Variants

Article number	Thread	DN	PN	a/f	Price
103534	Rp 1	25.0	40 bar	41 mm	285,87 € / Stk
103532	Rp 1/2	15.0	40 bar	26 mm	290,52 € / Stk
103533	Rp 3/4	20.0	40 bar	32 mm	294,00 € / Stk
103535	Rp 1 1/4	32.0	40 bar	50 mm	323,14 € / Stk
103536	Rp 1 1/2	40.0	25 bar	55 mm	342,35 € / Stk
103537	Rp 2	50.0	25 bar	70 mm	433,57 € / Stk
103538	Rp 2 1/2	65.0	25 bar	83 mm	607,71 € / Stk
103539	Rp 3	80.0	16 bar	98 mm	809,35 € / Stk

More Pictures

