


Datasheet for: 133127



Service unit 3-part »multifix«, Protective cage, Size 4, G 3/4

Service unit 3-part »multifix«, PC container, Protective cage, Size 4, G 3/4, Input pressure max. 16 bar, Control range 0.5-10 bar. Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Type number	FRL 44 S-10
Article number	133127
EAN/barcode	 4047322476164
Your price	395,58 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	255.0 mm
B	315.0 mm
Bowl	Polycarbonate container with protective cage
C	125.0 mm
Condensate drain	Semi-automatic
D	190.0 mm
DN	20.0
Filter rating	5.0 µm
Flow rate	9500 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Housing	Die-cast aluminium
Max. ambient temperature	60 °C
Max. control range	10.0 bar
Max. input pressure	16 bar
Max. internal air consumption	1.5 l/min (depending on secondary pressure)
Max. medium temperature	60 °C
Min. control range	0.5 bar
Page No.	HK093

Pressure gauge display max.	16.0 bar
Pressure gauge display min.	0.0 bar
Sealant	NBR
Series	multifix
Sight dome	PA
Size	4
Spring bonnet	POM-brass
Thread	G 3/4
air consumption	Yes

Variants

Article number	Thread	Housing	Filter rating	Flow rate	Size	DN	Price
133127	G 3/4	Die-cast aluminium	5.0 μm	9500 l/min	4	20.0	395,58 € / Stk
100586	G 1/4	Die-cast zinc	5.0 μm	1100 l/min	1	6.0	137,69 € / Stk
100587	G 3/8	Die-cast zinc	5.0 μm	1100 l/min	1	10.0	137,69 € / Stk
100588	G 1/2	Die-cast zinc	5.0 μm	3000 l/min	3	15.0	197,10 € / Stk
100589	G 3/4	Die-cast zinc	5.0 μm	3000 l/min	3	25.0	197,10 € / Stk
100590	G 1	Aluminium	40.0 μm	11300 l/min	5	25.0	507,88 € / Stk
133128	G 1	Die-cast aluminium	5.0 μm	9500 l/min	4	25.0	395,58 € / Stk

More Pictures

