


Datasheet for: 133152


Active charcoal filter »multifix«, Metal container, Size 4, G 1

Active charcoal filter »multifix« with metal container, 0.005 mg/m³, Size 4, G 1, Input pressure max. 16 bar, Temp. max. 60 °C . For filtering odours out of compressed air. The activated carbon absorbs the oil vapour molecules contained in the compressed air. A separate filter route prevents activated carbon particles from entering the air flow.

Type number	FA 45 M
Article number	133152
EAN/barcode	 4047322476416
Your price	286,34 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	85.0 mm
B	240.0 mm
Bowl	Metal container
C	58.0 mm
D	182.0 mm
DN	25.0
Filter element	Activated carbon-POM
Flow rate	3000 l/min
Flow rate measurement	At P ₁ = 6 bar and pressure drop Δ_p = 0.2 bar
Housing	Die-cast aluminium
Max. ambient temperature	60 °C
Max. input pressure	16 bar
Max. medium temperature	60 °C
Page No.	HK088
Residual oil content	0.005 mg/m ³
Sealant	NBR
Series	multifix
Size	4
Thread	G 1

Variants

Article number	Thread	Housing	Flow rate	Size	DN	Price
133152	G 1	Die-cast aluminium	3000 l/min	4	25.0	286,34 € / Stk
100543	G 1/4	Die-cast zinc	380 l/min	1	6.0	104,96 € / Stk
100544	G 1/2	Die-cast zinc	1500 l/min	3	15.0	154,81 € / Stk
133151	G 3/4	Die-cast aluminium	3000 l/min	4	20.0	286,34 € / Stk

More Pictures

