


Datasheet for: 133526


Stainless steel pressure regulator, 1.4401, G 1/4, 1.7 - 17.5 bar

Stainless steel pressure regulator, 1.4401, with secondary venting (reversible), Size 1, G 1/4, Control range 1.7 - 17.5 bar . Stainless steel regulators for use in the chemical industry, mining, plant construction and special machinery industries, pneumatics, etc. Pressure setting by hexagon head screw.

Type number	580RM1-14-17
Article number	133526
EAN/barcode	 4047322479103
Your price	401,56 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	64.0 mm
B	167.0 mm
C	50.0 mm
D	117.0 mm
Diaphragms	NBR/PTFE
Flow rate	2320 l/min
Flow rate measurement	At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p \leq 1$ bar
Housing	Stainless steel 1.4401 (AISI 316)
Max. ambient temperature	80 °C
Max. control range	17.5 bar
Max. input pressure	30 bar
Max. medium temperature	80 °C
Min. control range	1.7 bar
Page No.	HK147
Sealant	NBR
Size	1
Thread	G 1/4

Variants

Article number	Thread	Min. control range	Max. control range	Flow rate	Size	Price
133526	G 1/4	1.7 bar	17.5 bar	2320 l/min	1	401,56 € / Stk
133530	G 1/2	1.7 bar	17.5 bar	6175 l/min	3	503,39 € / Stk
133527	G 3/8	0.4 bar	4.0 bar	4900 l/min	1	401,56 € / Stk
133531	G 3/4	0.4 bar	4.0 bar	10195 l/min	3	503,39 € / Stk
133534	G 1	1.7 bar	17.5 bar	10195 l/min	4	1.358,07 € / Stk
133533	G 1	0.4 bar	4.0 bar	10195 l/min	4	1.358,07 € / Stk
133528	G 3/8	1.7 bar	17.5 bar	4900 l/min	1	401,56 € / Stk
133532	G 3/4	1.7 bar	17.5 bar	10195 l/min	3	503,39 € / Stk
133529	G 1/2	0.4 bar	4.0 bar	6175 l/min	3	503,39 € / Stk
133525	G 1/4	0.4 bar	4.0 bar	2320 l/min	1	401,56 € / Stk

More Pictures

