


Datasheet for: 101127



Service unit »ONE« with pressure switch, G 1/2

Service unit »ONE« with pressure switch, G 1/2, Input pressure max. 10 bar, Control range 0.5 - 8 bar, Temp. -10 °C to 50 °C. Multifunctional service unit with 6 or 7 functions in a single device: 3/2-way valve (manually operated), filter with automatic drain valve, air ports, pressure regulator, pressure gauge, soft start valve and optional pressure switch. This combination of extremely good flow rates and a wide range of functions integrated in a single, compact unit saves valuable space and is unmatched by any similar product available in the market! Soft starting independently of the load and easy replacement of the filter cartridge under pressure are just two of the other outstanding features of this amazing device.

Type number	533.313
Article number	101127
EAN/barcode	 4047322284837
Your price	402,49 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	165.5 mm
B	144.0 mm
C	35.0 mm
Filter rating	20.0 µm
Flow rate	4000 l/min
Flow rate measurement	At P ₂ = 6.3 bar and pressure drop Δ _p = 1 bar
Max. control range	8.0 bar
Max. input pressure	10 bar
Max. temperature range	50 °C
Medium	Pneumatics
Min. control range	0.5 bar
Min. temperature range	-10 °C
Operating voltage	24 V DC (for valves and pressure switch)
Page No.	HK136
Protection IP	IP 65

Series
Thread

ONE
G 1/2

Variants

Article number	Thread	Flow rate	Price
101127	G 1/2	4000 l/min	402,49 € / Stk
101125	G 1/4	2400 l/min	398,84 € / Stk
101126	G 3/8	3300 l/min	398,84 € / Stk

More Pictures

