


Datasheet for: 133399


Blocking valve pneumat. actuated, single-acting NC, FKM, Rp 2

Blocking valve pneumat. actuated, single-acting, NC, nickel-plated brass, Temp. -20°C to 150°C, Control pressure 4.2-8 bar, Rp 2. 2/2-way check valves, specially designed for automated industrial plant engineering. A low-price, compact, space-saving and reliable alternative to ball valves with a pneumatic rotary actuator. These valves have a full bore and - owing to the optimised design - only minimal flow losses. They are controlled by means of filtered compressed air.

Type number	351.957
Article number	133399
EAN/barcode	 4047322477963
Your price	404,20 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	NAMUR interface, direct: 2 x G 1/8
DN	50.0
H	109.0 mm
Housing	Nickel-plated brass
Internal parts	Nickel-plated brass
L	207.0 mm
Max. operating pressure	10 bar
Max. operating temperature	150 °C
Max. pilot pressure	8.0 bar
Min. operating temperature	-20 °C
Min. pilot pressure	4.2 bar
Mounting position	Any
Page No.	HK345
Sealant	FKM
Spring	Stainless steel
Thread	Rp 2
Version	single-acting - spring to close

Variants

Article number	Thread	DN	Price
133399	Rp 2	50.0	404,20 € / Stk
103735	Rp 3/8	10.0	116,26 € / Stk
103736	Rp 1/2	15.0	128,02 € / Stk
103737	Rp 3/4	20.0	145,84 € / Stk
103738	Rp 1	25.0	168,44 € / Stk
133398	Rp 1 1/2	40.0	286,78 € / Stk
133397	Rp 1 1/4	32.0	229,26 € / Stk

More Pictures

