


Datasheet for: 100530


Pre-filter »multifix« PC container, Protective cage, Size 3 G 1/2

 Pre-filter »multifix« with PC container and protective cage, 0.3 μm , Size 3, G 1/2, Input pressure max. 16 bar, Temp. max. 60 °C . For filtering out solid impurities larger than 0.3 μm .

Type number	FV 33 S
Article number	100530
EAN/barcode	 4047322132350
Your price	152,24 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	68.8 mm
B	185.8 mm
Bowl	Polycarbonate container with protective cage
C	38.5 mm
Condensate drain	Semi-automatic
D	147.3 mm
DN	15.0
Efficiency	99.999 %
Filter element	Paper-POM
Filter rating	0.3 μm
Flow rate	500 l/min
Flow rate measurement	At $P_1 = 6$ bar and pressure drop $\Delta_p = 0.02$ bar
Housing	Die-cast zinc
Max. ambient temperature	60 °C
Max. input pressure	16 bar
Max. medium temperature	60 °C
Page No.	HK085
Sealant	NBR
Series	multifix
Size	3

Thread

G 1/2

Variants

Article number	Thread	Housing	Flow rate	Size	DN	Price
100530	G 1/2	Die-cast zinc	500 l/min	3	15.0	152,24 € / Stk
100529	G 1/4	Die-cast zinc	160 l/min	1	6.0	96,91 € / Stk
133116	G 1	Die-cast aluminium	2000 l/min	4	25.0	205,85 € / Stk
133115	G 3/4	Die-cast aluminium	2000 l/min	4	20.0	205,85 € / Stk

More Pictures
