

Datasheet for: 101578


Active charcoal filter with differential pressure gauge, G 1/2

Active charcoal filter with differential pressure gauge, 0.005 mg/m³, G 1/2, Input pressure 4 - 16 bar, Temp. 5 °C to 60 °C . For adsorbing vaporous media. A micro-filter must be connected upstream if dried air is not available.

Type number	431.3106
-------------	----------

Article number	101578
----------------	--------

EAN/barcode	 4047322087087
-------------	--

Your price	296,11 € / Stk
------------	----------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	83.0 mm
B1	344.0 mm
B2	245.0 mm
C	57.0 mm
D	263.0 mm
Filter element	Activated carbon
Flow rate	500 l/min
Flow rate measurement	At P ₁ = 6 bar and pressure drop $\Delta_p = 0.5\%$
Housing	Aluminium
Max. ambient temperature	60 °C
Max. indicating range of differential press. gauge	2.0 bar
Max. input pressure	16 bar
Max. medium temperature	60 °C
Min. ambient temperature	5 °C
Min. indicating range of differential press. gauge	0.0 bar

Min. input pressure	4.0 bar
Min. medium temperature	5 °C
Page No.	HK139
Residual oil content	0.005 mg/m ³
Thread	G 1/2
filter bowl	Aluminium

Variants

Article number	Thread	Flow rate	Price
101578	G 1/2	500 l/min	296,11 € / Stk
101576	G 1/4	500 l/min	297,17 € / Stk
101577	G 3/8	500 l/min	296,58 € / Stk
101579	G 3/4	1000 l/min	335,25 € / Stk
101580	G 1	1500 l/min	462,34 € / Stk
101581	G 1 1/4	2650 l/min	517,44 € / Stk
101582	G 1 1/2	4150 l/min	568,00 € / Stk
101583	G 2	6650 l/min	707,89 € / Stk

More Pictures

