


Datasheet for: 100569


**Service unit 2-part »multifix« with PC container, Size 3, G 3/4**

Service unit 2-part »multifix« with polycarbonate container, Size 3, G 3/4, Input pressure max. 16 bar, Control range 0.5 - 10 bar . Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Type number	CL 34 K-HA
Article number	100569
EAN/barcode	 4047322345309
Your price	152,96 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	134.8 mm
B	246.3 mm
Bowl	Polycarbonate container
C	99.0 mm
Condensate drain	Semi-automatic
D	147.3 mm
DN	20.0
Filter rating	5.0 $\mu$ m
Flow rate	3500 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc
Max. ambient temperature	60 °C
Max. control range	10.0 bar
Max. input pressure	16 bar
Max. medium temperature	60 °C
Min. control range	0.5 bar
Page No.	HK091
Pressure gauge display max.	16.0 bar

Pressure gauge display min.	0.0 bar
Sealant	NBR
Series	multifix
Sight dome	PA
Size	3
Spring bonnet	POM-brass
Thread	G 3/4

## Variants

Article number	Thread	Housing	Filter rating	Flow rate	Size	DN	Price
100569	G 3/4	Die-cast zinc	5.0 $\mu\text{m}$	3500 l/min	3	20.0	152,96 € / Stk
100570	G 1	Aluminium	40.0 $\mu\text{m}$	10500 l/min	5	25.0	469,14 € / Stk
100567	G 3/8	Die-cast zinc	5.0 $\mu\text{m}$	1100 l/min	1	10.0	90,78 € / Stk
100566	G 1/4	Die-cast zinc	5.0 $\mu\text{m}$	1100 l/min	1	6.0	86,75 € / Stk
100568	G 1/2	Die-cast zinc	5.0 $\mu\text{m}$	3500 l/min	3	15.0	152,96 € / Stk

## More Pictures

