

Datasheet for: 100497


Filter regulator »multifix«, 40 µm, Size 5, G 1, 0.5 - 10 bar

Filter regulator »multifix« with metal container, Viewing tube and press. gauge, 40 µm, Size 5, G 1, Input pressure max. 20 bar . Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator. The pressure setting can be locked by pushing the button down.

Type number	C 55 M-SR
-------------	-----------

Article number	100497
----------------	--------

EAN/barcode	
-------------	--



4047322179751

Your price	300,30 € / Stk
------------	----------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	100.0 mm
B	383.7 mm
Bowl	Metal container with viewing tube
C	128.0 mm
Condensate drain	Semi-automatic
D	255.7 mm
DN	25.0
Filter rating	40.0 µm
Flow rate	12000 l/min
Flow rate measurement	At P ₁ = 8 bar, P ₂ = 6 bar and pressure drop Δ _p = 1 bar
Housing	Aluminium
Max. ambient temperature	60 °C
Max. control range	10.0 bar
Max. input pressure	20 bar
Max. internal air consumption	0,5 l/min (depending on secondary pressure)
Max. medium temperature	60 °C
Min. control range	0.5 bar

Page No.	HK082
Pressure gauge display max.	16.0 bar
Pressure gauge display min.	0.0 bar
Sealant Series	NBR multifix
Size	5
Spring bonnet	POM-brass
Thread	G 1
air consumption	Yes

Variants

Article number	Thread	Housing	Filter rating	Flow rate	Size	Price
100497	G 1	Aluminium	40.0 μm	12000 l/min	5	300,30 € / Stk
100493	G 1/4	Die-cast zinc	5.0 μm	1500 l/min	1	81,20 € / Stk
100494	G 3/8	Die-cast zinc	5.0 μm	1500 l/min	1	81,20 € / Stk
100495	G 1/2	Die-cast zinc	5.0 μm	3500 l/min	3	107,98 € / Stk
100496	G 3/4	Die-cast zinc	5.0 μm	3500 l/min	3	109,04 € / Stk
133109	G 3/4	Die-cast aluminium	5.0 μm	12500 l/min	4	256,76 € / Stk
133110	G 1	Die-cast aluminium	5.0 μm	12500 l/min	4	256,76 € / Stk

More Pictures

