



Datasheet for: 113908


Suction/pressure hose, Lightweight design, Hose Ø 56.4x50

Suction and pressure hose, Lightweight design, Temperature -15°C to 60°C, Hose Ø 56.4x50 mm, PN at 23 °C max. 4 bar, Roll of 50 m . Transparent PVC spiral hose with green, impact-resistant, hard PVC spiral and smooth inner layer (prevents sediment). Applications: Construction industry, agriculture, engineering, gardening and landscaping

Type number	SDL-050
Article number	113908
EAN/barcode	 4047322400701
Your price	302,50 € / Role

Minimum order quantity

Price Unit	1
Quantity Unit	Role
Packaging Unit	1
Content	50 m
Minimum order quantity	1

Productdata

Max. operating pressure at 23 °C	4.0 bar
Max. temperature range	60 °C
Min. bending radius	230.0 mm
Min. temperature range	-15 °C
Page No.	HK919
Reel length	50 m
Tube I.D.	50 mm
Wall thickness	3.2 mm

Variants

<i>Article number</i>	<i>Tube I.D.</i>	<i>Wall thickness</i>	<i>Max. operating pressure at 23 °C</i>	<i>Min. bending radius</i>	<i>Reel length</i>	<i>Price</i>
113908	50 mm	3.2 mm	4.0 bar	230.0 mm	50 m	302,50 € / Role
113903	20 mm	2.3 mm	6.0 bar	80.0 mm	50 m	139,00 € / Role
113907	40 mm	2.9 mm	5.0 bar	180.0 mm	25 m	124,75 € / Role
113906	38 mm	2.8 mm	5.0 bar	160.0 mm	50 m	237,00 € / Role
113904	25 mm	2.3 mm	5.0 bar	105.0 mm	50 m	145,00 € / Role
113905	32 mm	2.4 mm	5.0 bar	135.0 mm	50 m	185,50 € / Role