

## Datasheet for: 158758



**Stainless steel ball valve, Pneumatic actuation drive, Rp 1 1/2**

Stainless steel ball valve, Pneumatic actuation drive, double-acting, Operating temp. -20 °C to 150 °C, Rp 1 1/2, PN max. 64 bar . Ball valves with pneumatic actuator. Pneumatic, double-piston, part-turn actuator, double-rocker principle.

|             |           |
|-------------|-----------|
| Type number | 351.514-1 |
|-------------|-----------|

|                |        |
|----------------|--------|
| Article number | 158758 |
|----------------|--------|

EAN/barcode



4047322635196

|            |                |
|------------|----------------|
| Your price | 407,52 € / Stk |
|------------|----------------|

**Minimum order quantity**

|                        |       |
|------------------------|-------|
| Price Unit             | 1     |
| Quantity Unit          | Stk   |
| Packaging Unit         | 1     |
| Content                | 1 Stk |
| Minimum order quantity | 1     |

**Productdata**

|                                     |  |
|-------------------------------------|--|
| A                                   | 198.0 mm   |
| Angle of rotation                   | 90 °   |
| B                                   | 200.7 mm   |
| DN                                  | 40.0   |
| L                                   | 105.0 mm   |
| Material actuator                   | Anodised aluminium   |
| Material ball valve                 | Stainless steel 1.4401/1.4301/1.4310/1.4408, with ISO flange |
| Max. Operating pressure ball valve  | 150 °C   |
| Max. operating temperature actuator | 80 °C  |
| Max. pilot pressure actuator        | 8.4 bar  |
| Min. Operating pressure ball valve  | -20 °C   |
| Min. operating temperature actuator | -20 °C   |
| PN                                  | 64 bar   |
| Page No.                            | HK304  |
| Recommended pilot pressure          | 5.6 bar  |
| Sealant actuator                    | NBR  |

Sealant ball valve  
Thread  
Valve adapter  
Version

PTFE / FKM  
Rp 1 1/2  
Integrated to NAMUR  
double-acting

## Variants

| Article number | Thread   | DN   | PN      | Price          |
|----------------|----------|------|---------|----------------|
| 158758         | Rp 1 1/2 | 40.0 | 64 bar  | 407,52 € / Stk |
| 158754         | Rp 1/2   | 15.0 | 100 bar | 235,50 € / Stk |
| 158757         | Rp 1 1/4 | 32.0 | 64 bar  | 353,72 € / Stk |
| 158755         | Rp 3/4   | 20.0 | 100 bar | 272,84 € / Stk |
| 158756         | Rp 1     | 25.0 | 100 bar | 298,68 € / Stk |
| 158753         | Rp 3/8   | 10.0 | 100 bar | 231,04 € / Stk |
| 158759         | Rp 2     | 50.0 | 40 bar  | 543,12 € / Stk |

## More Pictures

