

Datasheet for: 101589


Active charcoal filter without differential press. gauge, G 1 1/4

Active charcoal filter without differential pressure gauge, 0.005 mg/m³, G 1 1/4, Input pressure 4 - 16 bar, Temp. 5 °C to 60 °C. For adsorbing vaporous media. A micro-filter must be connected upstream if dried air is not available.

Type number	431.5410
-------------	----------

Article number	101589
----------------	--------

EAN/barcode	
-------------	--



4047322087193

Your price	410,44 € / Stk
------------	----------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	118.0 mm
B2	430.0 mm
C	72.0 mm
D	568.0 mm
Filter element	Activated carbon
Flow rate	2650 l/min
Flow rate measurement	At P ₁ = 6 bar and pressure drop Δ _p = 0.5%
Housing	Aluminium
Max. ambient temperature	60 °C
Max. input pressure	16 bar
Max. medium temperature	60 °C
Min. ambient temperature	5 °C
Min. input pressure	4.0 bar
Min. medium temperature	5 °C
Page No.	HK139
Residual oil content	0.005 mg/m ³
Thread	G 1 1/4
filter bowl	Aluminium

Variants

Article number	Thread	Flow rate	Price
101589	G 1 1/4	2650 l/min	410,44 € / Stk
101584	G 1/4	500 l/min	192,30 € / Stk
101585	G 3/8	500 l/min	191,73 € / Stk
101586	G 1/2	500 l/min	191,26 € / Stk
101587	G 3/4	1000 l/min	229,91 € / Stk
101588	G 1	1500 l/min	355,76 € / Stk
101590	G 1 1/2	4150 l/min	466,15 € / Stk
101591	G 2	6650 l/min	598,81 € / Stk

More Pictures

