


Datasheet for: 103101


Ball valve, Basic design, IT/IT, nickel-plated brass, G 2 1/2

Ball valve, Manual lever, Basic design, IT/IT, nickel-plated brass, Operating temp. -20°C to 150°C, G 2 1/2, DN 65, PN max. 18 bar . Applications: Compressed air, water, non-toxic and non-corrosive gases, heating systems and air conditioning systems.

Type number	329.10-R
Article number	103101
EAN/barcode	 4047322397407
Your price	153,71 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	197.0 mm
B	115.0 mm
Ball	Chrome-plated brass
Ball seal	PTFE
DN	65.0
E	24.0 mm
F	24.0 mm
Hand lever	Galvanised steel, painted red
L	134.5 mm
Material	Nickel-plated brass
Operating temperature	-20 °C to 150 °C (no steam)
PN	18 bar
Page No.	HK268
Standard thread	G-thread acc. to DIN EN ISO 228-1, tolerance class B
Stem seal	NBR / FKM (Seal package consists of 2 O-rings)
Thread	G 2 1/2
Thread material	Nickel-plated brass

Variants

Article number	Thread	DN	PN	Price
103101	G 2 1/2	65.0	18 bar	153,71 € / Stk
103095	G 1/2	15.0	50 bar	9,79 € / Stk
103094	G 3/8	10.0	50 bar	9,13 € / Stk
103093	G 1/4	8.0	50 bar	8,99 € / Stk
103099	G 1 1/2	40.0	30 bar	47,92 € / Stk
103102	G 3	80.0	16 bar	233,08 € / Stk
103098	G 1 1/4	32.0	30 bar	32,24 € / Stk
103100	G 2	50.0	25 bar	73,54 € / Stk
103096	G 3/4	20.0	40 bar	13,66 € / Stk
103097	G 1	25.0	40 bar	20,00 € / Stk

More Pictures

