


Datasheet for: 100464



Pressure regulator pneumatic remote controlled »multifix«, G 1

Pressure regulator pneumatic remote controlled »multifix«, without pressure gauge, Size 5, G 1, Input pressure max. 16 bar. Diaphragm pressure regulator, self-relieving, with pneumatic remote control. The pressure is set with a pilot pressure regulator (1:1 ratio). The output pressure corresponds to the set pressure of the pilot pressure regulator. Either a standard or a precision pressure regulator can be used to regulate the pilot pressure.

Type number	RI 55
Article number	100464
EAN/barcode	 4047322392372
Your price	153,83 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	100.0 mm
B	112.0 mm
C	60.0 mm
D	52.0 mm
DN	25.0
Flow rate	12500 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Aluminium
Max. ambient temperature	60 °C
Max. input pressure	16 bar
Max. internal air consumption	0,5 l/min (depending on secondary pressure)
Max. medium temperature	60 °C
Page No.	HK080
Pilot air connection	G 1/4
Sealant	NBR
Series	multifix
Size	5
Thread	G 1

air consumption

Yes

Variants

Article number	Thread	Pilot air connection	Housing	Flow rate	Size	DN	Price
100464	G 1	G 1/4	Aluminium	12500 l/min	5	25.0	153,83 € / Stk
100462	G 1/4	G 1/8	Die-cast zinc	1800 l/min	1	6.0	79,83 € / Stk
100463	G 1/2	G 1/4	Die-cast zinc	4800 l/min	3	15.0	108,89 € / Stk
133106	G 1	G 1/4	Die-cast aluminium	12500 l/min	4	25.0	135,05 € / Stk
133105	G 3/4	G 1/4	Die-cast aluminium	12500 l/min	4	20.0	135,05 € / Stk

More Pictures

