

Datasheet for: 100516



Filter »multifix«, Polycarbonate container, 40 μm , Size 5, G 1

 Filter »multifix« with polycarbonate container, 40 μm , Size 5, G 1, Input pressure max. 16 bar, Medium / ambient temp. max. 60 °C . Centrifugal separators with a sintered filter element.

Type number F 55 K-HA

Article number 100516

EAN/barcode



4047322344227

Your price 156,89 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	100.0 mm
B	305.8 mm
Bowl	Polycarbonate container
C	52.0 mm
Condensate drain	Semi-automatic
D	253.8 mm
DN	25.0
Filter rating	40.0 μm
Flow rate	8000 l/min
Flow rate measurement	At $P_1 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Aluminium
Max. ambient temperature	60 °C
Max. input pressure	16 bar
Max. medium temperature	60 °C
Page No.	HK084
Series	multifix
Size	5
Thread	G 1

Variants

Article number	Thread	Housing	Filter rating	Flow rate	DN	Size	Price
100516	G 1	Aluminium	40.0 μm	8000 l/min	25.0	5	156,89 € / Stk
100514	G 1/2	Die-cast zinc	5.0 μm	4000 l/min	15.0	3	52,04 € / Stk
100513	G 3/8	Die-cast zinc	5.0 μm	2100 l/min	10.0	1	28,96 € / Stk
100515	G 3/4	Die-cast zinc	5.0 μm	4000 l/min	20.0	3	52,04 € / Stk
100512	G 1/4	Die-cast zinc	5.0 μm	2100 l/min	6.0	1	28,96 € / Stk

More Pictures

