

## Datasheet for: 103268


**Ball valve heavy duty design, Manual lever, IT/IT, G 2**

Ball valve heavy duty design, Manual lever, IT/IT, nickel-plated brass, Operating temp. -20 °C to 130 °C, G 2, PN max. 63 bar . Applications: Compressed air, water, neutral and non-toxic gases, fuel oil (light distillate), fuel oil (heavy), lubricating oils, diesel oils.

Type number	3350.09
Article number	103268
EAN/barcode	 4047322216104
Your price	157,03 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	175.0 mm
B	115.5 mm
Ball	Chrome-plated brass
Ball seal	PTFE
DN	50.0
E	20.5 mm
F	20.5 mm
Hand lever	Aluminium, painted black
Housing	Nickel-plated brass
L	121.0 mm
Max. operating temperature	130 °C
Min. operating temperature	-20 °C
PN	63 bar
Page No.	HK273
Standard thread	G thread acc. to DIN EN ISO 228-1
Stem seal	PTFE
Thread	G 2
Thread material	Brass with a bare metal surface
a/f	69 mm

## Variants

Article number	Thread	DN	PN	a/f	Price
103268	G 2	50.0	63 bar	69 mm	157,03 € / Stk
103266	G 1 1/4	32.0	80 bar	49 mm	72,91 € / Stk
103264	G 3/4	20.0	80 bar	32 mm	31,34 € / Stk
103270	G 3	80.0	40 bar	100 mm	256,26 € / Stk
103265	G 1	25.0	80 bar	39 mm	49,28 € / Stk
103267	G 1 1/2	40.0	80 bar	56 mm	91,09 € / Stk
103261	G 1/4	8.0	80 bar	18 mm	13,63 € / Stk
103263	G 1/2	15.0	80 bar	26 mm	20,51 € / Stk
103262	G 3/8	10.0	80 bar	21 mm	16,32 € / Stk
103269	G 2 1/2	65.0	40 bar	85 mm	194,65 € / Stk

## More Pictures

