

Datasheet for: 116556


2/2-way solenoid valve »2S« NC, pilot operated, 230 V, 50 Hz

2/2-way solenoid valve »2S«, Stainless steel, NC, pilot operated, 230 V, 50 Hz, Medium temp. max. 80°C/90°C, G 1, PN 0.5 - 10 bar . Standard series available in two different versions: -Directly operated -Pilot-operated Connector socket, form A acc. to ISO 4400, for all valves with a G 3/8 or G 1/2 thread except valve types 3 and 4. Special connector socket (similar to form B) for all valves with a G 1/8 or G 1/4 thread except valve types 3 and 4. Medium temperature max. 80 °C when used with water or oils, max. 90 °C when used with air.

Type number	MV 1543 ES
-------------	------------

Article number	116556
----------------	--------

EAN/barcode	
-------------	--



4047322324298

Your price	157,20 € / Stk
------------	----------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	70.0 mm
B	92.0 mm
C	124.0 mm
DN	25
Housing	Stainless steel 1.4301
Internal parts	Stainless steel
Max. operating pressure	10 bar
Min. operating pressure	0.5 bar
Page No.	HK330
Page No. AS	AS051
Protection IP	IP 65
Sealant	FPM
Standard thread	G thread acc. to DIN EN ISO 228-1
Thread	G 1
Type	3
Valve seat	Stainless steel 1.4301

Variants

Article number	Thread	DN	Price
116556	G 1	25	157,20 € / Stk
116552	G 1/2	15	102,33 € / Stk
116554	G 3/4	20	125,82 € / Stk

More Pictures

