


## Datasheet for: 102829


**2/2-way solenoid valve, NO, directly operated, 230 V, 50 - 60 Hz**

2/2-way solenoid valve brass, NO, directly operated, 230 V, 50 - 60 Hz, Medium temperature -25 °C to 80 °C, G 1/4, PN - 9 bar . Standard series, proven over many years, available in three different versions - Directly operated - Combined operation - Pilot-operated For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Type number	MV 2215
Article number	102829
EAN/barcode	 4047322159982
Your price	158,02 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	80.0 mm
B	40.0 mm
DN	3.2
Electrical connection	ISO 4400; cable socket (Pg 11P)
Function	normally open (NO)
Housing	Brass
Internal parts	Stainless steel
Max. ambient temperature	55 °C
Max. medium temperature	80 °C
Max. operating pressure	9 bar
Min. ambient temperature	-25 °C
Min. medium temperature	-25 °C
Page No.	HK317
Protection IP	IP65 (with connector socket fitted)
Sealant	NBR
Standard thread	G thread acc. to DIN EN ISO 228-1
Thread	G 1/4
Type	2
Valve seat	Brass

## Variants

Article number	Thread	Max. operating pressure	Max. medium temperature	DN	Sealant	Type	Price
102829	G 1/4	9 bar	80 °C	3.2	NBR	2	158,02 € / Stk
102827	Rp 1/8	20 bar	80 °C	2.4	NBR	7	115,99 € / Stk
102828	Rp 1/8	20 bar	100 °C	2.4	FKM	1	140,57 € / Stk
102830	G 1/4	9 bar	100 °C	3.2	FKM	2	177,12 € / Stk

## More Pictures

