


Datasheet for: 100555



Mist oiler »multifix« with polycarbonate container, Size 5, G 1

Mist oiler »multifix« with polycarbonate container, Size 5, G 1, Input pressure max. 16 bar, Medium / ambient temp. max. 60 °C . Proportional lubricators, oil can be filled under pressure.

Type number	L 55 K
Article number	100555
EAN/barcode	 4047322155816
Your price	158,62 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	100.0 mm
B	324.3 mm
Bowl	Polycarbonate container
C	82.7 mm
D	241.6 mm
DN	25.0
Flow rate	18000 l/min
Flow rate measurement	At P ₁ = 6 bar and pressure drop Δ_p = 1 bar
Housing	Aluminium
Max. ambient temperature	60 °C
Max. input pressure	16 bar
Max. medium temperature	60 °C
Oil grade	CL 32 acc. to DIN 51517-ISO VG 32
Page No.	HK089
Sealant	NBR
Series	multifix
Sight dome	PA
Size	5
Thread	G 1

Variants

Article number	Thread	Housing	Flow rate	Size	DN	Price
100555	G 1	Aluminium	18000 l/min	5	25.0	158,62 € / Stk
100551	G 1/4	Die-cast zinc	1900 l/min	1	6.0	36,33 € / Stk
100552	G 3/8	Die-cast zinc	1900 l/min	1	10.0	36,33 € / Stk
100553	G 1/2	Die-cast zinc	5000 l/min	3	15.0	58,13 € / Stk
100554	G 3/4	Die-cast zinc	5000 l/min	3	20.0	58,13 € / Stk

More Pictures

