

Datasheet for: 103430


Stainless steel ball valve, 1-piece, Reduced passage, G 2

Stainless steel ball valve 1.4401/1.4408, 1-piece, Reduced passage, Operating temp. -20 °C to 150 °C, G 2, DN 32, PN max. 63 bar .

| | |
|----------------|--|
| Type number | 398.09 |
| Article number | 103430 |
| EAN/barcode |  4047322082556 |
| Your price | 159,24 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|----------------------------|--|
| A | 155.0 mm |
| B | 85.0 mm |
| Ball | Stainless steel 1.4401 |
| Ball seal | PTFE (15 % glass fibre reinforced) |
| DN | 32.0 |
| Hand lever | Stainless steel 1.4301, with plastic coating |
| Housing | Stainless steel 1.4408 |
| L | 102.0 mm |
| Max. operating temperature | 150 °C |
| Min. operating temperature | -20 °C |
| Operating pressure | max. 63 bar (dependent on temperature) |
| Page No. | HK276 |
| Standard thread | G thread acc. to DIN EN ISO 228-1 |
| Stem seal | PTFE |
| Thread | G 2 |

Variants

| Article number | Thread | DN | Price |
|----------------|---------|------|----------------|
| 103430 | G 2 | 32.0 | 159,24 € / Stk |
| 103423 | G 1/4 | 5.0 | 39,03 € / Stk |
| 103424 | G 3/8 | 7.0 | 39,03 € / Stk |
| 103425 | G 1/2 | 9.2 | 33,90 € / Stk |
| 103426 | G 3/4 | 12.5 | 42,29 € / Stk |
| 103427 | G 1 | 15.0 | 53,35 € / Stk |
| 103428 | G 1 1/4 | 20.0 | 86,79 € / Stk |
| 103429 | G 1 1/2 | 25.0 | 117,07 € / Stk |

More Pictures

