


## Datasheet for: 113501


**Hose coupling set, PUR, Hose Ø 16x11, Length 10.0 m**

Hose coupling set, PUR, Safety coupling, Medium / ambient temperature max. 60 °C, Hose Ø 16x11, PN max. 16 bar, Length 10 m . Spiral or straight polyurethane hose, completely assembled with DN 7.6 safety coupling and steel plugs. Coupling Safety coupling made of steel / nickel-plated brass for high flow rates, specially designed for all applications susceptible to severe mechanical wear. Strong, impact and vibration-resistant design for demanding environments. Polyurethane hose Extremely flexible spiral hose with excellent kink resistance and insensitive to dirt. Combines high tear, tensile and impact strength with a long service life and optimal ageing qualities. This hose is additionally characterised by outstanding resistance to abrasion and resistance to UV. Not suitable for direct attachment to pulsating tools. We recommend using our vibration dampers, according to ISO 6150 § 7.1.

Type number	SKS 248.1610
Article number	113501
EAN/barcode	 4047322273947
Your price	200,85 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Hose size	16x11 mm
Material	Polyurethane (PUR)
Max. ambient temperature	60 °C
Max. medium temperature	60 °C
Max. operating pressure	16 bar
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK901
Page No. SK	SK093
Service length max.	10.0 m

## Variants

<i>Article number</i>	<i>Hose size</i>	<i>Service length max.</i>	<i>Price</i>
113501	16x11 mm	10.0 m	200,85 € / Stk
113502	16x11 mm	15.0 m	266,38 € / Stk
113500	12x8 mm	15.0 m	160,06 € / Stk
113499	12x8 mm	10.0 m	122,72 € / Stk