


## Datasheet for: 107423


**Quick-connect coupling I.D. 7.8, St. steel 1.4305, Sleeve I.D. 6**

Quick-connect coupling I.D. 7.8, Stainless steel 1.4305, Sleeve I.D. 6, Operating pressure - 35 bar, Temp. -15 °C to 200 °C . One-hand quick disconnect couplings, one side sealing, made of stainless steel 1.4305. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. These quick disconnect couplings are not suitable for direct attachment to pulsating tools. We recommend using our vibration dampers, according to ISO 6150 § 7.1. Areas of application: Pneumatic system, machine and plant engineering, manufacturing industry, medical technology, chemical / pharmaceutical industry, food technology, aerospace, mining, offshore.

Type number	243.70 A
Article number	107423
EAN/barcode	 4047322060448
Your price	160,44 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Ball	Stainless steel
Connection	I.D. 6
DN	7.8
Flow rate	1800 l/min (air)
Flow rate measurement	at 6 bar and $\Delta p = 0.5$ bar
Housing	Stainless steel 1.4305
Length	73.5 mm
Max. ambient temperature	200 °C
Max. medium temperature	200 °C
Min. ambient temperature	-15 °C
Min. medium temperature	-15 °C
Operating pressure	to 35 bar, maximum static working pressure (non-pulsating)
Page No.	HK547
Page No. SK	SK029
Retaining ring	Stainless steel

Sealant  
 Sleeve  
 Spring  
 Valve body  
 a/f

FKM  
 Stainless steel 1.4305  
 Stainless steel  
 Stainless steel 1.4305  
 19 mm

## Variants

<i>Article number</i>	<i>Connection</i>	<i>Price</i>
107423	I.D. 6	160,44 € / Stk
107424	I.D. 8	168,33 € / Stk
107425	I.D. 9	153,43 € / Stk
107426	I.D. 10	168,34 € / Stk
107427	I.D. 13	175,26 € / Stk

## More Pictures

