


Datasheet for: 101648

**Proportional control valve »posiflow«, 24 V DC, NC, G 3/8, DN 7.1**


Proportional control valve »posiflow«, for water / oil, 24 V DC, NC, G 3/8, DN 7.1, Operating pressure difference max. 1 bar . For electronic flow control. For all applications where the flow rate of a liquid or gas has to be controlled. The valve features a special magnet armature and is characterised by low friction and a high dynamic response. If the valve is combined with a plug amplifier: The maximum / minimum current and frequency can be adjusted by means of integrated potentiometers. A current ramp can also be connected and adjusted with a potentiometer. This facilitates a slow change in the flow rate, even if the setpoint changes suddenly. If the setpoint is < 200 mV ( < 0.4 / 4.4 mA), the piloting current is completely switched off, causing the valve to be de-energised (tightly closed function). We recommend combining these proportional valves with a plug amplifier. Benefits: - Compact and economical - Integrated temperature compensation - Precise control - Optimised flow with no water hammer - Ramp function assures a smooth response to step changes in the input signal - Disconnect function

Type number	PV 2026
Article number	101648
EAN/barcode	 4047322163491
Your price	200,98 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	85.0 mm
B	48.0 mm
C	97.0 mm
DN	7.1
Failsafe behaviour	Tight closure in case of loss of voltage
Housing	Brass
Internal parts	Stainless steel
Max. ambient temperature	75 °C
Max. medium temperature	90 °C

Max. operating pressure difference	1.0 bar
Medium	Air, neutral gases, water, oil
Min. ambient temperature	-10 °C
Min. medium temperature	-10 °C
Page No.	HK186
Piloting	Via plug amplifier to 10 V, to 20 mA, 4 to 20 mA
Pressure range	Vacuum to 8 bar
Sealant	FKM
Thread	G 3/8
Valve disc	FKM
Valve seat	Brass

## Variants

Article number	Thread	DN	Max. operating pressure difference	Price
101648	G 3/8	7.1	1.0 bar	200,98 € / Stk
101645	G 1/4	2.4	8.0 bar	184,24 € / Stk
101646	G 1/4	3.2	4.0 bar	184,24 € / Stk
101647	G 3/8	5.6	1.4 bar	200,98 € / Stk

## More Pictures

