


Datasheet for: 102832


2/2-way solenoid valve, NO, directly operated, 24 V DC, G 1/4

2/2-way solenoid valve brass, NO, directly operated, 24 V DC, Medium temperature -25 °C to 80 °C, G 1/4, PN - 5.5 bar . Standard series, proven over many years, available in three different versions - Directly operated - Combined operation - Pilot-operated For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Type number	MV 2215 G
Article number	102832
EAN/barcode	 4047322159999
Your price	160,60 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	80.0 mm
B	40.0 mm
DN	3.2
Electrical connection	ISO 4400; cable socket (Pg 11P)
Function	normally open (NO)
Housing	Brass
Internal parts	Stainless steel
Max. ambient temperature	55 °C
Max. medium temperature	80 °C
Max. operating pressure	5.5 bar
Min. ambient temperature	-25 °C
Min. medium temperature	-25 °C
Page No.	HK317
Protection IP	IP65 (with connector socket fitted)
Sealant	NBR
Standard thread	G thread acc. to DIN EN ISO 228-1
Thread	G 1/4
Type	2
Valve seat	Brass

Variants

Article number	Thread	Max. operating pressure	DN	Type	Price
102832	G 1/4	5.5 bar	3.2	2	160,60 € / Stk
102831	Rp 1/8	13 bar	2.4	7	131,22 € / Stk

More Pictures

