


## Datasheet for: 100979


**Filter »Standard« with metal container, 40  $\mu\text{m}$ , Size 4, G 1 1/2**

 Filter »Standard« with metal container, 40  $\mu\text{m}$ , Size 4, G 1 1/2, Input pressure max. 25 bar, Medium / ambient temperature max. 60°C . Centrifugal separators with a sintered filter element.

Type number	650 G/M
Article number	100979
EAN/barcode	 4047322110433
Your price	202,92 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	125.0 mm
Bowl	Metal container
C	36.5 mm
Condensate drain	Manuel
D	246.0 mm
DN	45.0
Filter rating	40.0 $\mu\text{m}$
Flow rate	12500 l/min
Flow rate measurement	At $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
H	105.0 mm
Housing	Die-cast zinc, painted silver
Max. ambient temperature	60 °C
Max. input pressure	25 bar
Max. medium temperature	60 °C
Page No.	HK125
Series	Standard
Size	4
Thread	G 1 1/2

## Variants

Article number	Thread	Filter rating	Flow rate	Size	DN	Price
100979	G 1 1/2	40.0 $\mu\text{m}$	12500 l/min	4	45.0	202,92 € / Stk
100972	G 1/4	5.0 $\mu\text{m}$	800 l/min	1	6.0	29,94 € / Stk
100973	G 3/8	5.0 $\mu\text{m}$	800 l/min	1	6.0	29,94 € / Stk
100974	G 3/8	40.0 $\mu\text{m}$	3100 l/min	2	10.0	56,27 € / Stk
100975	G 1/2	5.0 $\mu\text{m}$	4000 l/min	3	15.0	55,72 € / Stk
100976	G 3/4	5.0 $\mu\text{m}$	4000 l/min	3	20.0	112,75 € / Stk
100977	G 1	5.0 $\mu\text{m}$	4000 l/min	3	25.0	112,75 € / Stk
100978	G 1 1/4	40.0 $\mu\text{m}$	12500 l/min	4	40.0	235,42 € / Stk
100980	G 2	60.0 $\mu\text{m}$	30000 l/min	5	55.0	562,99 € / Stk

## More Pictures

