


Datasheet for: 102849


2/2-way solenoid valve, NO, force pilot operated, 230 V, Rp 3/4

2/2-way solenoid valve brass, NO, force pilot operated, 230 V, 50 - 60 Hz, Rp 3/4, NBR, Medium temp. -20 °C to 85 °C, PN - 9 bar . Standard series, proven over many years, available in three different versions - Directly operated - Combined operation - Pilot-operated For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Type number	MV 2218
Article number	102849
EAN/barcode	 4047322160223
Your price	203,21 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	80.0 mm
B	70.0 mm
DN	19.0
Electrical connection	ISO 4400; cable socket (Pg 11P)
Function	normally open (NO)
Housing	Brass
Internal parts	Stainless steel
Max. ambient temperature	50 °C
Max. medium temperature	85 °C
Max. operating pressure	9 bar
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK318
Protection IP	IP65 (with connector socket fitted)
Sealant	NBR
Standard thread	Rp thread acc. to ISO 7-1
Thread	Rp 3/4
Type	3
Valve seat	Brass

Variants

Article number	Thread	Max. medium temperature	DN	Sealant	Price
102849	Rp 3/4	85 °C	19.0	NBR	203,21 € / Stk
102845	Rp 3/8	85 °C	16.0	NBR	169,37 € / Stk
102846	Rp 3/8	120 °C	16.0	FKM	191,51 € / Stk
102847	Rp 1/2	85 °C	16.0	NBR	169,37 € / Stk
102848	Rp 1/2	120 °C	16.0	FKM	204,61 € / Stk
102850	Rp 3/4	120 °C	19.0	FKM	231,76 € / Stk
136148	Rp 1	85 °C	25.0	NBR	795,44 € / Stk
136149	Rp 1	120 °C	25.0	FKM	1.051,10 € / Stk
136150	Rp 1 1/4	85 °C	28.0	NBR	930,98 € / Stk
136151	Rp 1 1/2	85 °C	32.0	NBR	1.243,66 € / Stk

More Pictures

