


## Datasheet for: 125334


**Active charcoal filter »variobloc« Metal container, Size 2, G 1**

Active charcoal filter »variobloc« with metal container incl. viewing tube, 0.003 mg/m<sup>3</sup>, Size 2, G 1, Input pressure max. 20 bar . Activated carbon filters are used to absorb oil vapour from the compressed air. The incoming compressed air should be dry and free of impurities (upstream connection of a micro-filter is recommended).

Type number	VAK 26 M
Article number	125334
EAN/barcode	 4047322397902
Your price	203,46 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	124.0 mm
Air quality acc. to ISO 8573.1	Class 1 dirt, class 1 oil
B	193.0 mm
Bowl	Metal container with viewing tube
C	26.0 mm
Flow rate	1300 l/min
Flow rate measurement	At P <sub>1</sub> = 7 bar and pressure drop Δp = 0,1 bar
Max. ambient temperature	80 °C
Max. input pressure	20 bar
Max. medium temperature	50 °C
Page No.	WEB
Residual oil content	0.003 mg/m <sup>3</sup>
Series	variobloc
Size	2
Thread	G 1

## Variants

Article number	Thread	Flow rate	Size	Price
125334	G 1	1300 l/min	2	203,46 € / Stk
125331	G 3/8	1000 l/min	1	116,43 € / Stk
125333	G 3/4	1300 l/min	2	164,41 € / Stk
125330	G 1/4	800 l/min	1	116,43 € / Stk
125332	G 1/2	1200 l/min	2	164,41 € / Stk

## More Pictures

