


Datasheet for: 136152


2/2-way solenoid valve, NO, force pilot operated, 24 V DC, Rp 3/8

2/2-way solenoid valve brass, NO, force pilot operated, 24 V DC, Rp 3/8, FKM, Medium temp. -20 °C to 120 °C, PN - 9 bar . Standard series, proven over many years, available in three different versions - Directly operated - Combined operation - Pilot-operated For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Type number	MV 2236 G
Article number	136152
EAN/barcode	 4047322502825
Your price	203,72 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	80.0 mm
B	70.0 mm
DN	16.0
Electrical connection	ISO 4400; cable socket (Pg 11P)
Function	normally open (NO)
Housing	Brass
Internal parts	Stainless steel
Max. ambient temperature	50 °C
Max. medium temperature	120 °C
Max. operating pressure	9 bar
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK318
Protection IP	IP65 (with connector socket fitted)
Sealant	FKM
Standard thread	Rp thread acc. to ISO 7-1
Thread	Rp 3/8
Type	3
Valve seat	Brass

Variants

Article number	Thread	Max. medium temperature	DN	Sealant	Price
136152	Rp 3/8	120 °C	16.0	FKM	203,72 € / Stk
102851	Rp 3/8	85 °C	16.0	NBR	190,20 € / Stk
102852	Rp 1/2	85 °C	16.0	NBR	190,20 € / Stk
102853	Rp 3/4	85 °C	19.0	NBR	221,24 € / Stk
136153	Rp 1/2	120 °C	16.0	FKM	217,77 € / Stk
136154	Rp 3/4	120 °C	19.0	FKM	245,84 € / Stk

More Pictures

